

exclusive

# amoiré

TYPE II  
WALLCOVERING

**TYPE II** High durability, CCC-W-408D and W-101

**WEIGHT** 20 oz/ly (620 g/lm)

**WIDTH** 54" (137 cm)

**CONTENTS** 100% vinyl

**BACKING** Osnaburg

**PATTERN MATCH** Non-reverse hang, 35" (89 cm) vertical repeat, random match

**FIRE TEST** ASTM E84 Tunnel Test: Class A, flame spread 15, smoke developed 10 (test procedure is comparable to UL 723)

CAN/ULC S102 Tunnel Test: flame spread 15, smoke developed 75

NFPA 286 Corner Burn Test: meets requirements for flame spread, smoke developed and flashover

**LOW VOC** California Section 01350, CHPS, SCS Indoor Advantage™ Gold

**CONSTRUCTION WASTE MANAGEMENT** May be recyclable through reclamation

**MICROVENTING AVAILABLE** This product can be microvented with the Duravent process for breathability. You may specify this as an added feature.

#### ADDITIONAL PRODUCT ATTRIBUTES

Antimicrobial additives  
Cadmium and mercury free  
Contains no heavy metals  
Does not contain DEHP plasticizers  
Free of PBDE's (Brominated Flame Retardants)  
Manufacturing materials recovery and reuse program  
Water-based inks

**CUSTOM CAPABILITIES** Custom colors, weights and widths are available

**WARRANTY** Manufacturer warrants that for a period of five years from the installation of its commercial wallcovering there shall not be separation from their backings, exhibit stains caused by bleeding of impurities or support the growth of mildew when wallcoverings are installed properly on a sound wall, adequately maintained and used under normal conditions

**PRODUCT USE ADVISORY** This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make vinyl wallcovering cleanable and durable also render it low in permeability. Vinyl wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

